

BULK NAILS - FLUTED MASONRY



FLUTED MASONRY

- Flat Countersunk Head
- Diamond Point
- Fluted Shank

For fastening lumber to any type of concrete or masonry work. Predrilling may be necessary in some applications. For best holding power, choose a length that will penetrate 3/4" into the masonry. Solid blows at right angles provide the best results.

FLUTED MASONRY - TEMPER HARDENED							
Item #	Size	Length	Gauge	Head	Weight	Nails/lb	UPC
7P206		3/4"	9	5/16"	50 lb	230	95832007259
7P210		1"	9	5/16"	50 lb	180	95832007273
7P212		1 1/4"	9	5/16"	50 lb	147	95832007280
7P214		1 1/2"	9	5/16"	50 lb	125	95832007297
7P216		1 3/4"	9	5/16"	50 lb	108	95832007303
7P220		2"	9	5/16"	50 lb	96	95832007310
7P222		2 1/4"	9	5/16"	50 lb	86	95832007327
7P224		2 1/2"	9	5/16"	50 lb	78	95832007334
7P230		3"	9	5/16"	50 lb	65	95832007341
7P234		3 1/2"	9	1 1/32"	50 lb	47	95832007358
7P240		4"	9	3/8"	50 lb	35	95832007488